



# WMT5 ECO Boiler

Mains Fed • Wall-mounted • Hot Water Boiler



*trial it, love it, keep it!*

Request your no obligation 10 day trial

Call **01392 877 172** Email **hello@thirstywork.com**

**www.thirstywork.com/free-trial**

# WMT5 ECO Boiler

Wall-mounted model with ECO features



## COLOUR OPTIONS



Stainless Steel

## WATER OPTIONS



Hot

## INSTALLATION OPTIONS



Wall-mounted

## KEY FEATURES

- ✓ Designed to save time, energy and money
- ✓ Wall-mounted model
- ✓ Uninterrupted hot water supply
- ✓ Ideal for making up to 133 cups per hour
- ✓ Up to 5 litres per serving
- ✓ Space saving model
- ✓ High grade insulated tank for energy-efficiency
- ✓ Manually activated ECO mode saves energy by minimising the energy wasted during machine down-time
- ✓ Easy to clean
- ✓ Full filter change and servicing package
- ✓ With **pura** filtration
- ✓ Made with 95% recyclable material

The WMT5 wall-mounted hot water boiler is best in class for energy efficiency and reliability. The ECO Boiler incorporates a ½ tank 'ECO mode' function, designed to save energy by minimising the energy wasted during machine down-time. This mode is most effective in installations where the machine has a regular 'off' period.

Its compact footprint makes it suitable for locations where space is limited, saving work surface space. The WMT5 is an ideal boiling water solution for small to medium sized catering venues, canteens, and staff rooms, dispensing 24 litres per hour of hot water for up to 133 cups of tea or coffee.

## DIMENSIONS

Height:	448mm
Width:	325mm
Depth:	223mm

## FULL SPECIFICATION WMT5 ECO Boiler wall-mounted hot water boiler

Type	Wall-mounted - standard range
<b>CAPACITY, WEIGHTS AND DIMENSIONS</b>	
Capacity	24 litres
Unit dimensions	325mm (w) x 223mm (d) x 448mm (h)
Packed dimensions	410mm (w) x 330mm (d) x 480mm (h)
Packed weight	22kg
<b>CONSTRUCTION</b>	
Outer fabrication (body) construction	Stainless steel surround. Made with 95% recyclable material
Tank construction	Stainless steel 316L
Drip-tray construction	Plastic
<b>ELECTRICAL</b>	
Power rating	2.4kW
Voltage supply	2.4kW-230V-50Hz
Electrical supply	Single-phase, N and E (13A)
Plug type	UK standard 3-pin
Fitted cable length	1m
<b>PLUMBING</b>	
Water inlet connection	3/4" BSP
Food quality, flexible mains water hose	1.1m PTFE hose with 3/4BSP connection
Mains water pressure required (limits):	5 - 50psi (35 - 345kPa)
Overflow/waste connection	Front via removable drip-tray
<b>PERFORMANCE</b>	
Water temperature delivered	96°C (default)
Heat up time to working temperature	40 mins (full tank capacity)
Output per hour (@ default temperature setting)	24 litres
Rapid draw-off	5 litres
<b>FILTRATION</b>	
Taste and odour, sediment and reduces lime-scale	Yes
Filter benefits	Removes trace plastics in water down to 10 micron size
Max filter capacity	Up to 3,006 litres
<b>OTHER FEATURES</b>	
Insulated tank for minimal energy-loss	Yes
Over-boil and boil-dry protection	Yes fitted as standard
<b>STANDARDS AND APPROVALS</b>	
UL and NSF approved	Yes
CE Certified	Yes

*trial it, love it, keep it!*

Request your no obligation 10 day trial

Call **01392 877 172** Email **hello@thirstywork.com**

**www.thirstywork.com/free-trial**